

Millaco Acrylic Sprays

Product Information

Millaco acrylic spray is a fast drying refinishing paint with good protection against weathering and yellowing. This product is especially suited for the quick paint repair on cars and other vehicles. It sprays to give a tough durable acrylic coating. It is recommended to use Millaco primer filler as an undercoat



Properties:


It sprays to give a tough acrylic finish. It is advised to spray a sample first!



Pre-treatment / Cleansing:

Pre-cleansing with a good Panel Wipe

Process: Coating Procedure



Please read the directions for use!

Characteristics

Fast drying,
Weather Resistant
Good adhesion.

Colour Processing Conditions

Gloss Black, Matt Black, Satin Black
from +10°C and up to 80% relative air humidity.

Drying Times:

Set to touch Full hardness



after approx. 20—30 mins at 20° C.
after 24 hours at 20° C.

Directions for use:

Ensure surface to be sprayed is clean and free from any traces of corrosion, grease, oil or polishing agent etc. Lightly abrade the surface, shake the can vigorously for approx. 3 mins. prior to use and spray several light coats from 25 – 30cm, allowing a 10 – 15 mins. flash off time in between coats

After use, invert can and spray for a few seconds to clear the valve and nozzle. This prevents the aerosol from clogging up when using next time

Safety Information:

Only to be used in well ventilated areas. Keep away from sources of ignition, do not smoke, eat or drink. Keep out of the reach of children. **Caution!** Pressurised container.

Protect from sunlight and do not expose to temperatures exceeding 50°C.

For professional use only. **Caution!** Disposal only in accordance to the regulations of the environmental health authorities.

The data sheet is for information purposes only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.

MILLACO - Supplied in the UK by MONOFIL – Applied House, Fulflood Road, Havant, Hampshire. PO9 5AX
Tel: +44 (0) 239 2470909 - Fax: +44 (0) 239 2476340
Internet: www.monofil.co.uk e-mail: sales@monofil.co.uk