

## 1 Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: Private Label Smart Wheel Repair Fade Out Thinner Spray

1.2 Relevant identified uses of the substance or mixture and uses advised against  
No further relevant information available.

Application of the substance / the mixture Color spray

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Monofil Ltd  
Applied House, Fullflood Road  
Havant, Hampshire  
PO9 5AX

1.4 Emergency telephone number: Tel: 02392 470909

## 2 Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam, Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container. May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn: Harmful

R20: Harmful by inhalation.



Xi: Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or cracking.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Trade name: Private Label Smart Wheel Repair Fade Out Thinner Spray

(Contd. of page 1)

**Hazard pictograms**

GHS02 GHS07

**Signal word** Danger**Hazard-determining components of labelling:**acetone  
ethyl acetate**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container. May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurised container: Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

**3 Composition/information on ingredients****3.2 Chemical characterization: Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether F+ R12 Flam. Gas 1, H220; Press. Gas, H280	25-50%
CAS: 108-94-1 EINECS: 203-631-1	cyclohexanone Xi R20 R10 Flam. Liq. 3, H226; Acute Tox. 4, H332	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.n.: 01-2119471330-49	acetone Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	15-20%

(Contd. on page 3)

**Trade name:** Private Label Smart Wheel Repair Fade Out Thinner Spray

CAS: 141-78-6		ethyl acetate		(Cont. of page 2)
EINECS: 205-500-4		Xn R36; F R11		15-20%
Reg.nr.: 01-2119475103-46		R66-67		
<i>Additional information: For the wording of the listed risk phrases refer to section 16.</i>				

#### 4 First aid measures

##### 4.1 Description of first aid measures

###### General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

###### After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Generally the product does not irritate the skin.

###### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Firefighting measures

##### 5.1 Extinguishing media

Suitable extinguishing agents: CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

##### 5.3 Advice for firefighters

###### Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

#### 6 Accidental release measures

##### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

##### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

##### 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleaning agents

##### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Cont. on page 4)

**Trade name:** Private Label Smart Wheel Repair Fade Out Thinner Spray

See Section 13 for disposal information.

(Cont'd. of page 3)

## 7 Handling and storage

### 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.

### Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.  
Information about storage in one common storage facility: Store away from foodstuffs.

#### Further information about storage conditions:

Do not seal receptacle gas tight.  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

Storage class: 2 B

7.3 Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

##### 115-10-6 dimethyl ether

WEL (1) Short-term value: 958 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

##### 108-94-1 cyclohexanone

WEL (1) Short-term value: 82 mg/m<sup>3</sup>, 20 ppm  
Long-term value: 41 mg/m<sup>3</sup>, 10 ppm  
S8, BAKGV

##### 67-64-1 acetone

WEL (1) Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

##### 141-78-6 ethyl acetate

WEL (1) Short-term value: 400 ppm  
Long-term value: 200 ppm

(Cont'd. on page 5)

**Trade name:** Private Label Smart Wheel Repair Fade Out Thinner Sprav

(Contd. of page 4)

**Ingredients with biological limit values:****108-94-1 cyclohexanone**

**BSGV (1)** 2 mmol/mol creatinine  
 Medium: urine  
 Sampling time: post shift  
 Parameter: cyclohexanol

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes.  
 Avoid contact with the eyes and skin.

**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

**Form:** Aerosol  
**Colour:** Colourless  
**Odour:** Characteristic  
**Odour threshold:** Not determined.

**pH-value:** Not determined.

(Contd. on page 6)

Trade name: Private Label Smart Wheel Repair Fade Out Thinner Spray

(Contd. of page 5)

· <b>Change in condition</b>	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-24 °C
· <b>Flash point:</b>	< 1 °C (DIN EN ISO 1523:2002)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	235 °C (DIN 51794)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	1.3 Vol %
Upper:	18.6 Vol %
· <b>Vapour pressure at 20 °C:</b>	5200 hPa
· <b>Density at 20 °C:</b>	0.792 g/cm <sup>3</sup> (DIN EN ISO 2811-1)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	100.0 %
VOC (EC)	792.2 g/l
· <b>9.2 Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

(Contd. on page 7)

Trade name: Private Label Smart Wheel Repair Fade Out Thinner Spray

(Contd. of page 6)

**11 Toxicological information****11.1 Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****108-94-1 cyclohexanone**

Oval	LD50	1535 mg/kg (rat)
Dermal	LD50	948 mg/kg (rabbit)

**Primary irritant effect:**

on the skin: No irritant effect.

on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

**12 Ecological information****12.1 Toxicity**

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

**Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

**13 Disposal considerations****13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging
14 06 03*	other solvents and solvent mixtures

**Uncleaned packaging:**



Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Trade name: Private Label Smart Wheel Repair Fade Out Thinner Spray

(Contd. of page 7)

**14 Transport information**

- 14.1 UN-Number - ADR, IMDG, IATA	UN1950
- 14.2 UN proper shipping name - ADR - IMDG - IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
- 14.3 Transport hazard class(es) - ADR	
	
- Class - Label	2 3F Gases 2.1
- IMDG, IATA	
	
- Class - Label	2.1 2.1
- 14.4 Packing group - ADR, IMDG, IATA	Void
- 14.5 Environmental hazards: - Marine pollutant:	No
- 14.6 Special precautions for user - Danger code (Kewler): - EMS Number:	Warning: Gases, - F-D,S-U
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
- Transport/Additional information:	
- ADR - Transport category - Tunnel restriction code	2 D
- UN "Model Regulation":	UN1950, AEROSOLS, 2.1

**15 Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Class	Share in %
NK	50-100

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)



**Trade name:** Private Label Smart Wheel Repair Fade Out Thinner Spray

(Contd. of page 8)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

#### Relevant phrases

H220 Extremely flammable gas.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H280 Contains gas under pressure; may explode if heated.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H336 May cause drowsiness or dizziness.

R10 Flammable.  
 R11 Highly flammable.  
 R12 Extremely flammable.  
 R20 Harmful by inhalation.  
 R36 Irritating to eyes.  
 R66 Repeated exposure may cause skin dryness or cracking.  
 R67 Vapours may cause drowsiness and dizziness.

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organization  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 Flam. Gaz 1: Flammable gases, Hazard Category 1  
 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1  
 Press. Gaz: Gases under pressure: Compressed gas  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Flam. Liq. 3: Flammable liquids, Hazard Category 3  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

\* Data compared to the previous version altered.