

## 1 Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: Private label Smart Wheel Repair Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against  
No further relevant information available.

Application of the substance / the mixture Color spray

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Monofil Ltd  
Applied House  
Fullood Road  
Havant, Hampshire  
PO9 5AX

1.4 Emergency telephone number: Tel:

## 2 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



**Xi: Irritant**

R36: Irritating to eyes.



**Xi: Sensitising**

R43: May cause sensitisation by skin contact.



**F+ Extremely flammable**

R12: Extremely flammable.

R52/53-66-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

Trade name: Private label Smart Wheel Repair Primer

(Cont'd. of page 1)

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

**Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02 GHS05 GHS07

**Signal word Danger****Hazard-determining components of labelling:**

butanol

acetone

bisphenole

xylene

**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurized container. May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container. Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains epoxy constituents. May produce an allergic reaction.

**2.3 Other hazards****Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

(Cont'd. on page 3)

Trade name: Private label Smart Wheel Repair Primer

(Cont'd. of page 2)

**3 Composition/information on ingredients****3.2 Chemical characterization: Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether F+ R12 Flam. Gas 1, H220; Press. Gas, H280	2,5-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-15%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67 Flam. Liq. 3, H226; STOT SE 3, H336	3-10%
CAS: 1380-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylole Xi R20/21; Xi R38 R10 Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	3-10%
CAS: 78-83-1 EINECS: 201-145-0 Reg.nr.: 01-2119484609-23	butanol Xi R37/38-41 R10-67 Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	5-10%
	Mixture of 77% zinc bis(orthophosphate) (CAS 7779-90-0), 2% zinc oxide (CAS 1314-13-2) and 21% non-hazardous ingredients N R51/53 Aquatic Chronic 2, H411	2,5-3%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10 Flam. Liq. 3, H226	2,5-3%
CAS: 25068-38-0	bisphenole Xi R36/38; Xi R43 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	1-2,5%
CAS: 100-41-4 EINECS: 202-849-4	Ethylbenzene Xi R20; F R11 Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-2,5%
CAS: 64742-93-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Xi R65; Xi R37; N R51/53 R10-66-67 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	0,3-2%
CAS: 16267-17-0 EC number: 605-296-0	Condensation products of dimerised fatty acids, C18-unsaturated, with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine Xi R43 Skin Sens. 1, H317	0,1-0,3%

(Cont'd. on page 4)

**Trade name:** Private label Smart Wheel Repair Primer

(Contd. of page 3)

**Additional information:** For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

##### 4.1 Description of first aid measures

###### After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

###### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Firefighting measures

##### 5.1 Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

##### 5.3 Advice for firefighters

###### Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

#### 6 Accidental release measures

##### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

##### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

##### 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleaning agents

##### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

##### 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

##### Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

(Contd. on page 5)

- 01

**Trade name:** Private label Smart Wheel Repair Primer

(Cont'd. of page 4)

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

**Storage class:** 2 B

**7.3 Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**115-10-6 dimethyl ether**

WEL (j) Short-term value: 958 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

**67-64-1 acetone**

WEL (j) Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

**123-86-4 n-butyl acetate**

WEL (j) Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

**1330-20-7 xylene**

WEL (j) Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; B4GV

**78-83-1 butanol**

WEL (j) Short-term value: 231 mg/m<sup>3</sup>, 75 ppm  
Long-term value: 154 mg/m<sup>3</sup>, 50 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL (j) Short-term value: 348 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

**100-41-4 Ethylbenzene**

WEL (j) Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

**Ingredients with biological limit values:**

**1330-20-7 xylene**

(Cont'd. on page 6)



**Trade name:** Private label Smart Wheel Repair Primer

(Contd. of page 5)

**BAGV (l)** 650 mmol/mol creatinine  
 Medium: urine  
 Sampling time: post shift  
 Parameter: methyl hippuric acid

**Additional information:** The lists valid during the making were used as basis.

## 8.2 Exposure controls

### Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes.  
 Avoid contact with the eyes and skin.

#### Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

#### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

##### Appearance:

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

(Contd. on page 7)

Trade name: Private label Smart Wheel Repair Primer

(Cont'd. of page 6)

pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-24 °C
Flash point:	< 0 °C (DIN EN ISO 1523:2002)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	235 °C (DIN 51794)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	18.6 Vol %
Vapour pressure at 20 °C:	5200 hPa
Density at 20 °C:	0.835 g/cm <sup>3</sup> (DIN EN ISO 2811-1)
Relative density:	Not determined.
Vapour density:	Not determined.
Evaporation rate:	Not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	79.9 %
Water:	0.1 %
VOC (EC)	667.0 g/l
Solids content (weight-%):	19.8 %
9.2 Other information	No further relevant information available.

### 10 Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:  
Possible in traces.  
Nitrogen oxides  
Hydrogen chloride (HCl)  
Carbon monoxide

(Cont'd. on page 8)

08

**Trade name:** Private label Smart Wheel Repair Primer

Nitrogen oxides (NOx)

(Contd. of page 7)

### 11 Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity:

##### LD/LC50 values relevant for classification:

##### 1330-20-7 xylene

Oral	LD50	5700 mg/kg (rat)
------	------	------------------

##### Primary irritant effect:

on the skin: No irritant effect.

on the eye: Irritating effect.

Sensitization: Sensitization possible through skin contact.

##### Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

### 12 Ecological information

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

##### Ecotoxicological effects:

Remark: Harmful to fish

##### Additional ecological information:

##### General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

##### 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

### 13 Disposal considerations

#### 13.1 Waste treatment methods

##### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

14 06 03*	other solvents and solvent mixtures
-----------	-------------------------------------

15 01 04	metallic packaging
----------	--------------------

(Contd. on page 9)





Trade name: Private label Smart Wheel Repair Primer

(Contd. of page 8)

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

#### 14 Transport information

14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es) ADR	
	
Class Label	2 - 5F Gases 2.1
IMDG, IATA	
	
Class Label	2.1 2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number:	Warning: Gases. - F-D,S-U
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Transport category Tunnel restriction code	2 D
UN "Model Regulation":	UN1950, AEROSOLS, 2.1

(Contd. on page 10)

Trade name: Private label Smart Wheel Repair Primer

(Cont'd. of page 9)

### 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Class	Share in %
NK	50-100

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H220 Extremely flammable gas.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H280 Contains gas under pressure; may explode if heated.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.  
 R11 Highly flammable.  
 R12 Extremely flammable.  
 R20 Harmful by inhalation.  
 R20/21 Harmful by inhalation and in contact with skin.  
 R36 Irritating to eyes.  
 R36/38 Irritating to eyes and skin.  
 R37 Irritating to respiratory system.  
 R37/38 Irritating to respiratory system and skin.  
 R38 Irritating to skin.  
 R41 Risk of serious damage to eyes.  
 R43 May cause sensitisation by skin contact.  
 R51/53 Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment.  
 R65 Harmful; may cause lung damage if swallowed.  
 R66 Repeated exposure may cause skin dryness or cracking.  
 R67 Vapours may cause drowsiness and dizziness.

#### Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organization  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Cont'd. on page 11)

according to 1907/2006/EC, Article 31

Printing date 27.03.2014

Version number 13

Revision: 27.03.2014

Trade name: Private label Smart Wheel Repair Primer

(Contd. of page 10)

VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 Flam. Gas 1: Flammable gases, Hazard Category 1  
 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1  
 Press. Gas: Gases under pressure: Compressed gas  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Flam. Liq. 3: Flammable liquids, Hazard Category 3  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
 Skin Sens. 1: Sensitization - Skin, Hazard Category 1  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3  
 - \* Data compared to the previous version altered.

08